





Wired Series				
Choose the right Internet security solution	Model			
	X8	X16	X32	XU
Key Features				
Suggested Use	Telecommuter/ Remote office	Remote office	Remote office	Remote office
Performance				
Concurrent Users	8	16	32	Unlimited
Throughput (FW/VPN)	190/35	190/35	190/35	190/35
Remote Access Users	1	10	15	25
Concurrent Connections	8,000	8,000	8,000	8,000
Security				
FireWall-I	✓	✓	✓	✓
SmartDefense Intrusion Prevention	✓	✓	✓	✓
Application Intelligence	✓	✓	✓	✓
Instant Messaging Security	✓	✓	✓	✓
P2P Security	✓	✓	✓	✓
Microsoft Network Protocol Security	✓	✓	✓	✓
Integrated Antivirus	✓	✓	✓	✓
HTTP support	✓	✓	✓	✓
FTP support	✓	✓	✓	✓
SMTP support	✓	✓	✓	✓
POP3 support	✓	✓	✓	✓
IMAP support	✓	✓	✓	✓
Custom TCP/UDP port scanning	✓	✓	✓	✓
Zip/TAR/GZ File Support	✓	✓	✓	✓
Unlimited file size inspection	✓	✓	✓	✓
Streaming Antivirus	✓	✓	✓	✓
Anti-Spam*	✓	✓	✓	✓
Anti-Spyware	✓	✓	✓	✓
Web filtering*	✓	✓	✓	✓
Denial of Service Security	✓	✓	✓	✓

Anti-Spoofing	✓	✓	✓	✓
Port-based/Tag Based VLANs	✓	✓	✓	✓
Total Access Protection integration with Integrity	✓	✓	✓	✓
802.1x Port-Based Authentication	✓	✓	✓	✓
User Quarantine on Authentication Failure	✓	✓	✓	✓
Hotspot Authentication/Authorization	✓	✓	✓	✓
RADIUS based Dynamic VLAN Assignment	✓	✓	✓	✓
VPN				
AES Encryption	✓	✓	✓	✓
3DES	✓	✓	✓	✓
DES	✓	✓	✓	✓
Pre-shared secret Site-to-Site Authentication	✓	✓	✓	✓
Check Point Internal Certificate Authority certificate Site-to-Site Authentication	✓	✓	✓	✓
x.509 Certificate Site-to-Site Authentication	✓	✓	✓	✓
Domain-based Site-to-Site VPN	✓	✓	✓	✓
Route-based Site-to-Site VPN	✓	✓	✓	✓
VPN Community Participation	✓	✓	✓	✓
Remote Access VPN Server	✓	✓	✓	✓
SecuRemote VPN Client License	✓	✓	✓	✓
Hardware VPN Client	✓	✓	✓	✓
Manual Login	✓	✓	✓	✓
Automatic Login	✓	✓	✓	✓
RADIUS authentication	✓	✓	✓	✓
Pre-shared Secret authentication	✓	✓	✓	✓
SecureID authentication**	✓	✓	✓	✓
LDAP/Active Directory**	✓	✓	✓	✓
TACACS authentication**	✓	✓	✓	✓
XAUTH authentication**	✓	✓	✓	✓

Certificate-based authentication**	✓	✓	✓	✓
IPSec NAT traversal	✓	✓	✓	✓
IPSec Compression	✓	✓	✓	✓
Hardware random number generator	✓	✓	✓	✓
L2TP over IPSec	✓	✓	✓	✓
Networking				
OSPF Routing	✓	✓	✓	✓
Source Routing	✓	✓	✓	✓
Static NAT	✓	✓	✓	✓
Hide Nat	✓	✓	✓	✓
Static or DHCP Address Assignment	✓	✓	✓	✓
PPPoE	✓	✓	✓	✓
Telstra	✓	✓	✓	✓
DHCP Server	✓	✓	✓	✓
DHCP Relay	✓	✓	✓	✓
Optional integrated ADSL modem	✓	✓	✓	✓
PPPoA	✓	✓	✓	✓
PPPoE	✓	✓	✓	✓
PPTP	✓	✓	✓	✓
EoA	✓	✓	✓	✓
ADSL Standards	ADSL2, ADSL2+, T.1413 G.DMT (G.992.1), G.Lite (G.992.2), ANNEX A (ADSL over POTS), ANNEX B (ADSL over ISDN)			
Bandwidth Management	✓	✓	✓	✓
Traffic Shaper	✓	✓	✓	✓
DiffServ Tagging	✓	✓	✓	✓
High Availability				
Gateway High Availability Ready	✓	✓	✓	✓
VPN Site Failover (MEP)	✓	✓	✓	✓
Backup ISP	✓	✓	✓	✓
Dialup Backup (requires external modem)	✓	✓	✓	✓
Dead Link Detection	✓	✓	✓	✓

Automatic Failover	✓	✓	✓	✓
Virtual IP	✓	✓	✓	✓
Wireless LAN				
IEEE 802.11b				
IEEE 802.11g				
Super-G***				
Wireless Security				
Wireless Range (regular mode)				
Wireless Range (extended mode)				
Wireless Multimedia (WMM) QoS				
Up to 4 Virtual access points				
Local Management				
Installation Wizard	✓	✓	✓	✓
Firewall Wizard	✓	✓	✓	✓
VPN Wizard	✓	✓	✓	✓
SmartDefense Wizard	✓	✓	✓	✓
Local logs	✓	✓	✓	✓
HTTPS remote management	✓	✓	✓	✓
Centralized Management				
SmartCenter UTM and Power	✓	✓	✓	✓
SmartLSM	✓	✓	✓	✓
Provider-I	✓	✓	✓	✓
SmartView Tracker Central Logging	✓	✓	✓	✓
Syslog	✓	✓	✓	✓
Eventia Analyzer event correlation	✓	✓	✓	✓
SmartUpdate	✓	✓	✓	✓
SmartDefense Services Updates	✓	✓	✓	✓
Out of Band Management				
CLI via SSH	✓	✓	✓	✓
CLI via Serial Port	✓	✓	✓	✓
SNMP Monitoring	✓	✓	✓	✓
Interfaces and Ports				
4 Ports 10/100 LAN Switch Ports	✓	✓	✓	✓

I WAN Port (ADSL or Ethernet)	✓	✓	✓	✓
I WAN2/DMZ Port	✓	✓	✓	✓
Serial Port	✓	✓	✓	✓
USB Print Server Ports	✓****	✓****	✓****	✓****
Hardware Specifications				
Dimensions	1.2 x 8 x 4.8 inches (3 x 20.3 x 12.2 cm)			
Weight	1.8 lbs (.82kg)			
Power	100-240 VAC, 50-60 Hz			
Regulatory Compliance	FCC Part 15 Class B, CE			
Warranty	1 Year Hardware			

* Web filtering is available via OPSEC integration

** Available when connecting to VPN-I UTM or VPN-I Power gateways

*** Requires clients to have select wireless NICs

**** USB Ports are available only in the models with integrated ADSL modem