





Wireless Series				
Choose the right Internet security solution	Model			
	W8	W16	W32	WU
Key Features				
Suggested Use	Telecommuter/ Remote office	Remote office	Remote office	Remote office
Performance				
Concurrent Users	8	16	32	Unlimited
Throughput (FW/VPN)	190/35	190/35	190/35	190/35
Remote Access Users	1	10	15	25
Concurrent Connections	8,000	8,000	8,000	8,000
Security				
FireWall-I	✓	✓	✓	✓
SmartDefense Intrusion Prevention	✓	✓	✓	✓
Application Intelligence	✓	✓	✓	✓
Instant Messaging Security	✓	✓	✓	✓
P2P Security	✓	✓	✓	✓
Microsoft Network Protocol Security	✓	✓	✓	✓
Integrated Antivirus	✓	✓	✓	✓
HTTP support	✓	✓	✓	✓
FTP support	✓	✓	✓	✓
SMTP support	✓	✓	✓	✓
POP3 support	✓	✓	✓	✓
IMAP support	✓	✓	✓	✓
Custom TCP/UDP port scanning	✓	✓	✓	✓
Zip/TAR/GZ File Support	✓	✓	✓	✓
Unlimited file size inspection	✓	✓	✓	✓
Streaming Antivirus	✓	✓	✓	✓
Anti-Spam*	✓	✓	✓	✓
Anti-Spyware	✓	✓	✓	✓
Web filtering*	✓	✓	✓	✓
Denial of Service Security	✓	✓	✓	✓

Anti-Spoofing	✓	✓	✓	✓
Port-based/Tag Based VLANs	✓	✓	✓	✓
Total Access Protection integration with Integrity	✓	✓	✓	✓
802.1x Port-Based Authentication	✓	✓	✓	✓
User Quarantine on Authentication Failure	✓	✓	✓	✓
Hotspot Authentication/Authorization	✓	✓	✓	✓
RADIUS based Dynamic VLAN Assignment	✓	✓	✓	✓
VPN				
AES Encryption	✓	✓	✓	✓
3DES	✓	✓	✓	✓
DES	✓	✓	✓	✓
Pre-shared secret Site-to-Site Authentication	✓	✓	✓	✓
Check Point Internal Certificate Authority certificate Site-to-Site Authentication	✓	✓	✓	✓
x.509 Certificate Site-to-Site Authentication	✓	✓	✓	✓
Domain-based Site-to-Site VPN	✓	✓	✓	✓
Route-based Site-to-Site VPN	✓	✓	✓	✓
VPN Community Participation	✓	✓	✓	✓
Remote Access VPN Server	✓	✓	✓	✓
SecuRemote VPN Client License	✓	✓	✓	✓
Hardware VPN Client	✓	✓	✓	✓
Manual Login	✓	✓	✓	✓
Automatic Login	✓	✓	✓	✓
RADIUS authentication	✓	✓	✓	✓
Pre-shared Secret authentication	✓	✓	✓	✓
SecureID authentication**	✓	✓	✓	✓
LDAP/Active Directory**	✓	✓	✓	✓
TACACS authentication**	✓	✓	✓	✓
XAUTH authentication**	✓	✓	✓	✓

Certificate-based authentication**	✓	✓	✓	✓
IPSec NAT traversal	✓	✓	✓	✓
IPSec Compression	✓	✓	✓	✓
Hardware random number generator	✓	✓	✓	✓
L2TP over IPSec	✓	✓	✓	✓
Networking				
OSPF Routing	✓	✓	✓	✓
Source Routing	✓	✓	✓	✓
Static NAT	✓	✓	✓	✓
Hide Nat	✓	✓	✓	✓
Static or DHCP Address Assignment	✓	✓	✓	✓
PPPoE	✓	✓	✓	✓
Telstra	✓	✓	✓	✓
DHCP Server	✓	✓	✓	✓
DHCP Relay	✓	✓	✓	✓
Optional integrated ADSL modem	✓	✓	✓	✓
PPPoA	✓	✓	✓	✓
PPPoE	✓	✓	✓	✓
PPTP	✓	✓	✓	✓
EoA	✓	✓	✓	✓
ADSL Standards	ADSL2, ADSL2+, T.1413 G.DMT (G.992.1), G.Lite (G.992.2), ANNEX A (ADSL over POTS), ANNEX B (ADSL over ISDN)			
Bandwidth Management	✓	✓	✓	✓
Traffic Shaper	✓	✓	✓	✓
DiffServ Tagging	✓	✓	✓	✓
High Availability				
Gateway High Availability Ready	✓	✓	✓	✓
VPN Site Failover (MEP)	✓	✓	✓	✓
Backup ISP	✓	✓	✓	✓
Dialup Backup (requires external modem)	✓	✓	✓	✓
Dead Link Detection	✓	✓	✓	✓

Automatic Failover	✓	✓	✓	✓
Virtual IP	✓	✓	✓	✓
Wireless LAN				
IEEE 802.11b	✓	✓	✓	✓
IEEE 802.11g	✓	✓	✓	✓
Super-G***	✓	✓	✓	✓
Wireless Security	IPSec VPN over WLAN, WEP, WPA, WPA-PSK, WPA2, 802.1x, Mac address filtering			
Wireless Range (regular mode)	Up to 109 yards (100m) indoors or 328 yards (300m) outdoors			
Wireless Range (extended mode)	Up to 328 yards (300m) indoors or 1094 yards (1 km) outdoors ***			
Wireless Multimedia (WMM) QoS	✓	✓	✓	✓
Up to 4 Virtual access points	✓	✓	✓	✓
Local Management				
Installation Wizard	✓	✓	✓	✓
Firewall Wizard	✓	✓	✓	✓
VPN Wizard	✓	✓	✓	✓
SmartDefense Wizard	✓	✓	✓	✓
Local logs	✓	✓	✓	✓
HTTPS remote management	✓	✓	✓	✓
Centralized Management				
SmartCenter UTM and Power	✓	✓	✓	✓
SmartLSM	✓	✓	✓	✓
Provider-1	✓	✓	✓	✓
SmartView Tracker Central Logging	✓	✓	✓	✓
Syslog	✓	✓	✓	✓
Eventia Analyzer event correlation	✓	✓	✓	✓
SmartUpdate	✓	✓	✓	✓
SmartDefense Services Updates	✓	✓	✓	✓
Out of Band Management				
CLI via SSH	✓	✓	✓	✓
CLI via Serial Port	✓	✓	✓	✓

SNMP Monitoring	✓	✓	✓	✓
Interfaces and Ports				
4 Ports 10/100 LAN Switch Ports	✓	✓	✓	✓
1 WAN Port (ADSL or Ethernet)	✓	✓	✓	✓
1 WAN2/DMZ Port	✓	✓	✓	✓
Serial Port	✓	✓	✓	✓
USB Print Server Ports	✓	✓	✓	✓
Hardware Specifications				
Dimensions	1.2 x 8 x 4.8 inches (3 x 20.3 x 12.2 cm)			
Weight	1.8 lbs (.82kg)			
Power	100-240 VAC, 50-60 Hz			
Regulatory Compliance	FCC Part 15 Class B, CE			
Warranty	1 Year Hardware			

* Web filtering is available via OPSEC integration

** Available when connecting to VPN-I UTM or VPN-I Power gateways

*** Requires clients to have select wireless NICs

**** USB Ports are available only in the models with integrated ADSL modem